

TECHNICAL DATA SHEET



PRODUCT INFORMATION

PRODUCT NAME VASOIL 2TC

DESCRIPTION **2 TC** is a lubricant intended for use in gasoline oil mixture employed in two-stroke engines. Its selective additive package provides high thermal stability, low deposit formation in the combustion chamber, the piston ring area and the exhaust system, while it reduce spark-plug fouling and ensures that the components remain clean.

PRODUCT USE

2 TC is recommended for all two-stroke gasoline engines in automotive, industrial and agriculture applications whether lubricated by separate pumped oil system or by petrol mixture. Use percentage 2 - 5 %, as recommended by the manufacture.

SPECIFICATIONS

2 TC meet the requirements of the following specifications:

- API TC
- JASO FB

CHARACTERISTICS (TYPICAL PROPERTIES)

VASOIL BRAND	SAE Viscosity Grade	Mass Density @ 15 C Kg / lt	Flash point ASTM C	Pour point D93 C	Kinematic Viscosity		Viscosity Index
					40 C	100 C	
2TC	20	0,87	170	-30	45,00	7,0	113
	30	0,88	180	-30	98,00	11,0	102

Vasoil Co Ltd

Nikou Pattichi 52 Street ,3071 Limassol, Cyprus.

Email vasoil@vasoil.com.cy , tel: 0035725334488

