

# TECHNICAL DATA SHEET



## PRODUCT INFORMATION

**PRODUCT NAME** VASOIL ATF DEX 3

**DESCRIPTION** **ATF DEX 3** is an extra high performance semi synthetic automatic transmission fluid formulated from high-quality base oils combined with a special additive including viscosity index improvers, antioxidants, and antifoams providing smooth and controlled friction wear characteristics.

## PRODUCT USE

**ATF DEX 3** is recommended for most passenger car and commercial automatic transmissions. It is also suitable for power steering systems, hydraulic applications, some manual transmissions where an automatic transmission fluid is specified and anywhere fluid with the following specification request.

## SPECIFICATIONS

**ATF DEX 3** meet the requirements of the following specifications:

GM DEXRON III D	MAN 339 TYPE Z-1 & V-1	VOITH 55,6335
GM DEXRON III G	ZF TE-ML- 02F,-03D,-04D,-09	FORD MERCON
MB 236,1 & MB 236,5	ZF TE-ML-11B,-14A,-17C	ALLISON C-4

## CHARACTERISTICS ( TYPICAL PROPERTIES )

VASOIL BRAND	SAE Viscosity Grade	Mass Density @ 15 C Kg / lt	Flash point ASTM C	Pour point D93 C	Kinematic Viscosity		Viscosity Index
					40 C	100 C	
<b>ATF DEX 3</b>		<b>0,863</b>	<b>180</b>	<b>-40</b>	<b>35</b>	<b>7.5</b>	<b>190</b>

