

# TECHNICAL DATA SHEET



## PRODUCT INFORMATION

**PRODUCT NAME** VASOIL ATF DEX D

**DESCRIPTION** ATF DEX D is formulated from high-quality HVI base oils combined with a special additive including viscosity index improvers, antioxidants, and antifoams providing smooth and controlled friction/wear characteristics. The product is a high performance, fluid for automatic transmissions in older vehicles specifying Dexron IID. It is also used as a hydraulic fluid in unique applications.

## PRODUCT USE

ATF DEX D can be used for some automatic and manual transmissions in passenger cars and light trucks specifying Dexron IID level performance as well as the related power steering systems. It is also suitable for use in some special hydraulic systems and anywhere fluid with the following specification request.

## SPECIFICATIONS

ATF DEX D meet the requirements of the following specifications:

GM DEXRON IID	Allison C-4	TYPE A, SUFFIX A
FORD MERCON	Cat TO - 2	

## CHARACTERISTICS ( TYPICAL PROPERTIES )

VASOIL BRAND	SAE Viscosity Grade	Mass Density @ 15 C Kg / lt	Flash point ASTM C	Pour point D93 C	Kinematic Viscosity		Viscosity Index
					40 C	100 C	
ATF DEX D		0,868	196	-40	38	7,3	160

Vasoil Co Ltd

Nikou Pattichi 52 Street ,3071 Limassol, Cyprus.

Email [vasoil@vasoil.com.cy](mailto:vasoil@vasoil.com.cy) , tel: 0035725334488

