

TECHNICAL DATA SHEET



PRODUCT INFORMATION

PRODUCT NAME VASOIL VASINAX GREASE AM

DESCRIPTION **VASINAX GREASE AM** is a high quality, lithium based grease, enriched with a special combination of additives which provides outstanding protection from oxidation, wear, rust and corrosion. It contains micro molybdenum disulfide which ensures dry lubrication properties when the grease is removed because of the high temperatures.

PRODUCT USE

VASINAX GREASE AM is recommended as a long life lubricant of automotive chassis fittings and bearings of all types, operating in severe service conditions in passenger cars, trucks, farm tractors and other equipment and machine tools.

ADVANTAGES

1. Outstanding retention under high pressure, heavy load and vibration conditions.
2. Fine lubrication properties and mechanical stability in a wide temperature range [-20° to +130° C].
3. Efficient oxidation stability.
4. Excellent protection from rust, wear and corrosion.
5. High resistance to water-washing.
6. Long service life.

SPECIFICATIONS

- NLGI 2, DIN 51825: KPRF 2 K-30

CHARACTERISTICS (TYPICAL PROPERTIES)

VASINAX GREASE A-M	ASTM	NLGI 2
Soap type		Lithium
Dry lubricant		Molybdenum disulfide
NLGI Number		2
Worked Penetration at 25 °C	D- 217	265-295
Drop Point, °C min	D- 566	200
Operation Temperature C		-30 to +130
Color		Black

Vasoil Co Ltd

Nikou Pattichi 52 Street ,3071 Limassol, Cyprus.

Email vasoil@vasoil.com.cy , tel: 0035725334488

