

TECHNICAL DATA SHEET



PRODUCT INFORMATION

PRODUCT NAME VASOIL VASPLEX GREASE

DESCRIPTION *VASPLEX GREASE is a high quality, calcium based grease, enriched with a special combination of additives which provides outstanding protection from oxidation, wear, rust, corrosion and excellent water resistance properties.*

PRODUCT USE

VASPLEX GREASE is recommended for lubrication of medium duty roller and plain bearings operating at a temperature from -10°C to +70°C and where water are present.

ADVANTAGES

1. High resistance to water washing.
2. Excellent fluidity in low temperature
3. Efficient oxidation stability.
4. Excellent protection from rust, wear and corrosion.

SPECIFICATIONS

DIN 51825 :K 2E-10

CHARACTERISTICS (TYPICAL PROPERTIES)

| VASPLEX GREASE | ASTM | |
|-----------------------------|--------|----------------|
| Soap type | | calcium |
| Operating temperature °C | | -10°C to +80°C |
| NLGI Number | | 2 |
| Worked Penetration at 25 °C | D- 217 | 265-295 |
| Drop Point, °C min | D- 566 | 95 |
| Color | | Fair brown |

Vasoil Co Ltd

Nikou Pattichi 52 Street ,3071 Limassol, Cyprus.

Email vasoil@vasoil.com.cy , tel: 0035725334488

