

# TECHNICAL DATA SHEET



## PRODUCT INFORMATION

**PRODUCT NAME** VASOIL HYDRAULIC OILS

**DESCRIPTION** **HYDRAULIC OILS** are blended from high viscosity index base oil and from special selected additives .to provide:

- 1.Anti-wear and EP Properties
- 2.Low pour points
- 3.Oxidation stability
- 4.Water resistance
- 5.Anti-foaming properties
- 6.Corrosion protection
- 7.Excellent filterability

## PRODUCT USE

**HYDRAULIC OILS** can be used for earth moving machinery hydraulic system, industrial hydraulic system and all hydraulic system recommended the following specification.

## SPECIFICATIONS

DIN 51524 PART 2 (HLP)	HOESCH HWN 2333	SPERRY VICKERS I-286-S
ARNOF NF E 48-603 (HM)	THYSSEN TH N-256132	U.S. STEEL 126
SIS SS 155434	CETOP RP 91 H (HM)	U.S. STEEL 127
VDMA 24318	SEB 181 222	DENISON TP 02100

## CHARACTERISTICS ( TYPICAL PROPERTIES )

VASOIL BRAND	ISO Viscosity Grade	Mass Density @ 15 C Kg / lt	Flash point ASTM C	Pour point D93 C	Kinematic Viscosity		Viscosity Index
					40 C	100 C	
HYDRAULIC OILS	22	0,831	220	-30	22	4,6	127
	32	0,872	220	-20	32	5,1	103
	46	0,876	230	-20	46	6,8	103
	68	0,883	240	-20	68	8,7	99
	100	0,890	250	-20	100	11,2	97
	150	0,891	263	-15	150	14,8	98

Vasoil Co Ltd

Nikou Pattichi 52 Street ,3071 Limassol, Cyprus.

Email [vasoil@vasoil.com.cy](mailto:vasoil@vasoil.com.cy) , tel: 0035725334488

