

TECHNICAL DATA SHEET



PRODUCT INFORMATION

PRODUCT NAME VASOIL LEOPARD CX

DESCRIPTION **LEOPARD CX** introduces oils for use in Diesel and Gasoline engines operating under very severe duty, or subject to deposit formation or excessive wear due to design characteristics. They are formulated from high quality base stock of high viscosity index and low pour point, treated with a carefully selected and balance percentage of the latest additives to impact superior detergency together with high dispersant antioxidant, antiwear and antifoam properties. The **LEOPARD CX** is marketed in Viscosity grades SAE 15W/40 & SAE 20W/50.

PRODUCT USE

LEOPARD CX, is specially formulated for **Diesel and Gasoline engines** operating under very severe duty and a normal drain period required. These Multigrade oil is able to give efficient lubrication when starting-up the engine, reducing friction, resist to sludge formation as well as enabling reduction of fuel consumption and air pollution.

SPECIFICATIONS

LEOPARD CX meets the requirements of the following specifications
 - API Service CF- 4 /CF/SJ - MAN 270 / 271 - DEUTZ DQC-1-05
 - ACEA E2/B2/A2 - MTU TYPE 1
 -MB 228.0/228.1 - VOLVO VDS

CHARACTERISTICS (TYPICAL PROPERTIES)

VASOIL BRAND	SAE	Mass	Flash	Pour	Kinematic	Viscosity	Viscosity	TBN
	Viscosity Grade	Density	point	point			Index	mgKOH/ g
		@ 15 C Kg / lt	ASTM C	D93 C	40 C	100 C		
LEOPARD CX	15W/40	0,892	230	-30	114	14.5	129	7.5
	20W/50	0,897	235	-25	166	18	120	7.5

