

TECHNICAL DATA SHEET



PRODUCT INFORMATION

PRODUCT NAME VASOIL LEOPARD DX

DESCRIPTION **LEOPARD DX** introduces improved oils for use in Diesel and Gasoline engines operating under very severe duty, or subject to deposit formation or excessive wear due to design characteristics. They are formulated from high quality base stock of high viscosity index and low pour point, treated with a carefully selected and balance percentage of the latest additives to impact superior detergency together with high dispersant antioxidant, antiwear and antifoam properties. The **LEOPARD DX** is marketed in Viscosity grades - SAE 15W/40 , SAE 15W/50 & SAE 20W/50.

PRODUCT USE

LEOPARD DX, is specially formulated for modern normally aspirated and supercharged turbo **Diesel and Gasoline engines** operating under very severe duty. These Multigrade oil is able to give efficient lubrication when starting-up the engine, reducing friction, resist to sludge formation as well as enabling reduction of fuel consumption and air pollution.

SPECIFICATIONS

LEOPARD DX meets the requirements of the following specifications:

API CG- 4 / CF- 4 / CF	API SL / SJ
ACEA E3 / E2	ACEA A3 / B3
MB 228.3 & MB 229.1	VOLVO VDS
MAN 3275	MTU Level 2

CHARACTERISTICS (TYPICAL PROPERTIES)

VASOIL BRAND	SAE Viscosity Grade	Mass Density @ 15 C Kg / lt	Flash point ASTM C	Pour point D93 C	Kinematic Viscosity		Viscosity Index	TBN mgKOH/ g
					40 C	100 C		
					LEOPARD DX	15W/40		
	15W/50	0,893	235	-30	140	18	143	8
	20W/50	0,897	235	-25	179	19	127	8

Vasoil Co Ltd

Nikou Pattichi 52 Street ,3071 Limassol, Cyprus.

Email vasoil@vasoil.com.cy , tel: 0035725334488

