

TECHNICAL DATA SHEET



PRODUCT INFORMATION

PRODUCT NAME VASOIL SUPER OUTBOARD

DESCRIPTION **SUPER OUTBOARD** is a superior performance semi-synthetic engine oil designed for watercooled 2-stroke out board engines. The combination of specially selected base oils with the latest technology additives results in superior product suitable for all 2-stroke outboard engines.

1. Anti-wear properties to ensure excellent engine protection
2. Excellent corrosion and storage protection
3. Outstanding engine cleanliness which reduces spark plug deposits

PRODUCT USE

SUPER OUTBOARD is recommended for use in premix and oil injection systems with both leaded and unleaded petrol for fuel/oil mixture ratios, as recommended by the engine manufacturer, up to 100:2.

SPECIFICATIONS

SUPER OUTBOARD requirement the following specifications

- BIA TC-W 3

CHARACTERISTICS (TYPICAL PROPERTIES)

VASOIL BRAND	SAE	Mass	Flash	Pour	Kinematic	Viscosity	Viscosity
	Viscosity Grade	Density	point	point			Index
		@ 15 C Kg / lt	ASTM C	D93 C	40 C	100 C	
SUPER OUTBOARD		0,871	94	-42	53	8,6	138

Vasoil Co Ltd

Nikou Pattichi 52 Street ,3071 Limassol, Cyprus.

Email vasoil@vasoil.com.cy , tel: 0035725334488

