

# TECHNICAL DATA SHEET



## PRODUCT INFORMATION

**PRODUCT NAME** VASOIL ULTRA-DIESEL 10W/40

**DESCRIPTION** **ULTRA-DIESEL** introduces a premium quality full synthetic low saps Diesel engine oil for use in EURO V and EURO VI engines with DPF and SCR nox reduction systems. Formulated from high quality synthetic base stock of high viscosity index , low NOACK and low pour point, treated with a carefully selected and balance percentage of the latest additives to impact superior detergency together with high dispersant antioxidant, antiwear and antifoam properties.  
The **ULTRA-DIESEL** is marketed in Viscosity grade - **SAE 10W/40 and SAE 5W/30**.

## PRODUCT USE

**ULTRA-DIESEL 10W/40** , is specially formulated for all types of low emissions diesel engines us EURO 4,5&6.and for modern normally aspirated and supercharged turbo Diesel engines operating under very severe duty. This Multigrade oil is able to give efficient lubrication when starting-up the engine, reducing friction, resist to sludge formation as well as enabling reduction of fuel consumption and air pollution.

## SPECIFICATIONS

**ULTRA-DIESEL 10W/40** meet the requirements of following specifications

ACEA E4 - 08/ E6	ACEA E7 / E9	CUMMINS CES 20081
API CJ - 4	VOLVO VDS 4 & VDS 3	CATERPILLAR ECF - 3
MB 228.51 / 228.31	MTU CATEGORY 3.1 & 2.1	MACK EO-O PREMIUM PLUS
MAN M3477, M3575 & M3271-1	RENAULT RLD – 3 / RLD-2	MACK EO-N PREMIUM PLUS
SCANIA LDF - 3	DETROIT DIESEL 93K218	DEUTZ DCQ-IV-10LA

## CHARACTERISTICS ( TYPICAL PROPERTIES )

VASOIL BRAND	SAE	Mass	Flash	Pour	Kinematic	Viscosity	Viscosity	TBN
	Viscosity	Density	point	point				mgK
	Grade	@ 15 C	ASTM	D93	40 C	100 C	Index	OH/ g
<b>ULTRA- DIESEL</b>	<b>10W/40</b>	<b>0,88</b>	<b>240</b>	<b>-30</b>	<b>100</b>	<b>15</b>	<b>157</b>	<b>12.8</b>
	<b>5W/30</b>	<b>0.86</b>	<b>230</b>	<b>-40</b>	<b>80</b>	<b>12</b>	<b>145</b>	<b>12.8</b>

Vasoil Co Ltd

Nikou Pattichi 52 Street ,3071 Limassol, Cyprus.

Email [vasoil@vasoil.com.cy](mailto:vasoil@vasoil.com.cy) , tel: 0035725334488

