

TECHNICAL DATA SHEET



PRODUCT INFORMATION

PRODUCT NAME VASOIL VAS-AIRCOM

DESCRIPTION **VAS-AIRCOM** is a fine quality air compressor lubricant, with a specially balanced additive combination. It is formulated to meet high-output, hot running reciprocating compressors. It protects from carbon and deposit formation.

1. Exceptional resistance to oxidation
2. Less carbon and deposit formation
3. Reduces fire and explosion hazards
4. Low volatility
5. Longer life of the lubricant
6. Excessive resistance to the formation of emulsion with water
7. Reduced operation and maintenance cost

PRODUCT USE

VAS-AIRCOM is recommended to be used with both, small and large compressors where the exhaust temperatures reach as high as 220 C.

SPECIFICATIONS

VAS-AIRCOM meet the requirements of the following specifications:

- DIN 51506 VD - L

CHARACTERISTICS (TYPICAL PROPERTIES)

VASOIL BRAND	ISO Viscosity Grade	Mass Density @ 15 C Kg / lt	Flash point ASTM C	Pour point D93 C	Kinematic Viscosity		Viscosity Index
					40 C	100 C	
VAS-AIRCOM	32	0,870	210	-12	32	5.46	106
	46	0,875	230	-12	46	6.86	104
	68	0,880	247	-12	68	8.80	102
	100	0,886	257	-10	100	11.38	100
	150	0,889	263	-9	150	14.83	98

Vasoil Co Ltd

Nikou Pattichi 52 Street ,3071 Limassol, Cyprus.

Email vasoil@vasoil.com.cy , tel: 0035725334488

