

TECHNICAL DATA SHEET



PRODUCT INFORMATION

PRODUCT NAME VASOIL VAS-REFRIGEROL LTS

DESCRIPTION VAS-REFRIGEROL LTS are superior lubricants formulated with special quality base synthetic oils. They are characterized by very low pour point and chemical stability. Due to these characteristics these lubricants are strongly recommended for refrigerator compressor lubrication.

- 1.Outstanding properties at very low temperatures
- 2.Excellent anti-oxidant properties
- 3.Very low pour and cloud point
- 4.Outstanding thermal and chemical stability
- 5.Effective protection from sludge and deposit formation
- 6.Long service life

PRODUCT USE

VAS-REFRIGEROL LTS is recommended for reciprocating and rotary refrigeration compressors operating at very low temperatures and requiring a lubricant able to maintain its lubrication properties and its thermal and chemical stability under heavy conditions. It is suitable with FREON.

SPECIFICATIONS

VAS-REFRIGEROL LTS meet the requirements of the following specifications:
- DIN 51503 KC

CHARACTERISTICS (TYPICAL PROPERTIES)

VASOIL BRAND	ISO Viscosity Grade	Mass Density @ 15 C Kg / lt	Flash point ASTM C	Pour point D93 C	Kinematic Viscosity		Viscosity Index
					40 C	100 C	
VAS-REFRIGEROL LTS	46	0,861	173	-56	46	7.6	132
	68	0,865	181	-54	68	10	131

Vasoil Co Ltd

Nikou Pattichi 52 Street ,3071 Limassol, Cyprus.

Email vasoil@vasoil.com.cy , tel: 0035725334488

