

TECHNICAL DATA SHEET



PRODUCT INFORMATION

PRODUCT NAME VASOIL VAS-REFRIGEROL

DESCRIPTION VAS-REFRIGEROL is a top quality, low pour point lubricant, produced from the refining of nophthionic base oils. Especially designed for lubrication of refrigeration reciprocating and rotary compressors and all types of refrigerants and refrigeration systems.

- High heat and chemical stability
- Strong lubricating film
- Low cloud point
- Ability of mixing with coolants
- High resistance to the formation of deposits
- Effective oxidation resistance

PRODUCT USE

VAS-REFRIGEROL, is used for the compressors cylinders lubrication of NH₃, freon, etc., and for applications under high moisture conditions.

SPECIFICATIONS

VAS-REFRIGEROL meet the requirements of the following specifications:
- DIN 51503 KA, BS 2626/75

CHARACTERISTICS (TYPICAL PROPERTIES)

VASOIL BRAND	ISO Viscosity Grade	Mass Density @ 15 C Kg / lt	Flash point ASTM C	Pour point D93 C	Kinematic Viscosity		Viscosity Index
					40 C	100 C	
VAS-REFRIGEROL	15	0,881	170	-42	15	3.5	116
	32	0,891	182	-40	32	5.5	108
	46	0,924	188	-36	46	6.9	105
	68	0,952	196	-33	68	8.7	99

