

TECHNICAL DATA SHEET



PRODUCT INFORMATION

PRODUCT NAME VASOIL VASLUB OILS

DESCRIPTION **VASLUB OILS** are premium quality mineral oils. They are refined to provide a high viscosity-index, good oxidation stability and improved demulsibility. They also have good temperature flow characteristics.

PRODUCT USE

VASLUB OILS are used for applications where additive-treated oils are not required. **VASLUB OILS** are recommended for the lubrication of plain and rolling – element bearings as well as for spur, bevel, helical and worm gearboxes where temperatures and loadings are moderate. The grade to be chosen should be that recommended by the system designer.

SPECIFICATIONS

- HVI Mineral Oils

CHARACTERISTICS (TYPICAL PROPERTIES)

VASOIL BRAND	ISO Viscosity Grade	Mass Density @ 15 C Kg / lt	Flash point ASTM C	Pour point D93 C	Kinematic Viscosity		Viscosity Index
					40 C	100 C	
VASLUB OILS	22	0,870	200	-10	22	4,2	90
	32	0,872	205	-10	32	5,4	103
	46	0,875	240	-10	46	6,8	101
	68	0,884	250	-10	68	8,7	100
	100	0,890	260	-10	100	11,4	100
	150	0,891	265	-10	150	15,0	100
	220	0,892	271	-10	220	18,9	96
	320	0,894	288	-8	320	24.1	96
	460	0,896	289	-8	460	30,6	96

Vasoil Co Ltd

Nikou Pattichi 52 Street ,3071 Limassol, Cyprus.

Email vasoil@vasoil.com.cy , tel: 0035725334488

