

TECHNICAL DATA SHEET



PRODUCT INFORMATION

PRODUCT NAME VASOIL VASREX SYNT

DESCRIPTION VASREX SYNT is full synthetic multipurpose gear lubricant for use in both synchronized manual transmissions, final drives and differentials where either API GL-4 or API GL-5 are specified.

PRODUCT USE

VASREX SYNT may be used in synchronised manual transmissions and final drives/differentials of a wide range of vehicles, commercial vehicle, construction equipment, passenger cars and anywhere API GL-4 or API GL-5 fluids are required

SPECIFICATIONS

VASREX SYNT OILS meet the requirements of the following specifications:

API GL-4 & API GL5	MAN M 3343 Type S	ZF TE-ML 02B / 05B / 07A
API MT-1	MAN 341 Type E-3	ZF TE-ML 12B / 16F / 17B
SAE J2360	MB 235.8	ZF TE-ML 19C / 21B
MIL-PRF-2105E	Mack GO-J	Scania STO 1:0
DAF	IVECO	ARVIN MERITOR 0-76-N

CHARACTERISTICS (TYPICAL PROPERTIES)

VASOIL BRAND	SAE Viscosity Grade	Mass Density @ 15 C Kg / lt	Flash ASTM C	Pour D93 C	Kinematic Viscosity		Viscosity Index
					40 C	100 C	
VASREX SYNT	75w/90	0,875	200	-45	83	17	223
	75w/80	0.87	200	-45	55	9	143

Vasoil Co Ltd

Nikou Pattichi 52 Street ,3071 Limassol, Cyprus.

Email vasoil@vasoil.com.cy , tel: 0035725334488

