

# TECHNICAL DATA SHEET



## PRODUCT INFORMATION

**PRODUCT NAME** VASOIL ULTRA SYNT

**DESCRIPTION** **ULTRA-SYNT** introduces premium quality full synthetic mid saps oil for use in the new generation of Gasoline and small Diesel engines operating under very severe duty, or excessive wear due to design characteristics.  
Formulated from high quality group III base stock treated with a carefully selected and balance percentage of the latest additives to impact superior detergency together with high dispersant antioxidant, antiwear and antifoam properties.

The **ULTRA-SYNT** is marketed in Viscosity grade - **SAE 5W/40 & 5W/30**.

## PRODUCT USE

**ULTRA-SYNT** , is specially formulated for modern normally aspirated and supercharged turbo Gasoline and small Diesel engines including those equipped with a DPF and 3 way catalysts.

## SPECIFICATIONS

**ULTRA-SYNT** meet the requirements of following specifications:

SAE 5W/40			SAE 5W/30
API SN / CF	ACEA C3 - 12	BMW LONGLIFE -04	API. SN / CF
MB 229.31 / 226.5	FORD WSS-M2C917A	PORCHE A 40	ACEA C2 - 12
VW 502 / 505.01	RN 0700 / RN 0710	GM DEXOS 2	RENAULT RN O700

## CHARACTERISTICS ( TYPICAL PROPERTIES )

VASOIL BRAND	SAE Viscosity Grade	Mass Density @ 15 C Kg / lt	Flash point ASTM C	Pour point D93 C	Kinematic Viscosity		Viscosity Index	TBN mgKOH/ g
					40 C	100 C		
ULTRA-SYNT	5W/40	0,875	220	-45	85.5	14.5	177	7.4
	5W/30	0,87	220	-45	70	12	169	7.4

Vasoil Co Ltd

Nikou Pattichi 52 Street ,3071 Limassol, Cyprus.

Email [vasoil@vasoil.com.cy](mailto:vasoil@vasoil.com.cy) , tel: 0035725334488

