

PRODUCT INFORMATION

PRODUCT NAME VASOIL LEOPARD DX MONOGRADES

DESCRIPTION LEOPARD DX Monogrades are lubricants for high output normally aspirated Diesel and Gasoline engines. They are formulated from top quality base stock of high Viscosity Index treated with a large percentage of additives to impart superior detergency together with high dispersant antioxidant, anticorrosion, antiwear antifoam properties.

PRODUCT USE

LEOPARD DX Monogrades oils range has a variety of uses as per each of its viscosity grades.

LEOPARD DX Monogrades 10W ,20W are used in hydraulic systems where such an oil is recommended.

LEOPARD DX Monogrades SAE 30, 40 are suitable for **Diesel** Engines, industrial transmissions where a non EP oil is required and every where a Monograde Oil is recommended.

SPECIFICATIONS

LEOPARD DX Monogrades meets the requirements of the following specifications

- API Service CF- 4 /CF/SJ - ACEA E2/B2/A2-96
- MAN 270 – MTU TYPE I - CAT TO-2

CHARACTERISTICS (TYPICAL PROPERTIES)

VASOIL BRAND	SAE Viscosity Grade	Mass Density @ 15 C Kg / lt	Flash point ASTM C	Pour point D93 C	Kinematic Viscosity		Viscosity Index	TBN mgKOH/ g
					40 C	100 C		
LEOPARD DX MONOGRADES	10W	0,870	210	-30	27	5,0	111	7.6
	20W	0,875	215	-25	46	7,0	109	7.6
	30	0,880	240	-20	111	12,0	97	7.6
	40	0,890	243	-20	139	14,0	97	7.6