

**PRODUCT INFORMATION**

**PRODUCT NAME** VASOIL LEOPARD RX 15W/40

**DESCRIPTION** **LEOPARD RX 15W/40** introduces improved oils for use in Diesel engines operating under very severe duty, or subject to deposit formation or excessive wear due to design characteristics. They are formulated from high quality base stock of high viscosity index, treated with a carefully selected additives to impact superior detergency together with high dispersant antioxidant, antiwear and antifoam properties.  
The **LEOPARD RX 15W/40** is marketed in Viscosity grade - SAE 15W/40.

**PRODUCT USE**

**LEOPARD RX 15W/40** , is specially formulated for modern normally aspirated and supercharged turbo **Diesel engines** operating under very severe duty. These Multigrade oil is able to give efficient lubrication when starting-up the engine, reducing friction, resist to sludge formation as well as enabling reduction of fuel consumption and air pollution.

**SPECIFICATIONS**

**LEOPARD RX 15W/40** meets the requirements of the following specifications:

ACEA E3 / B3

**CHARACTERISTICS ( TYPICAL PROPERTIES )**

<b>VASOIL BRAND</b>	<b>SAE Viscosity Grade</b>	<b>Mass Density @ 15 C Kg / lt</b>	<b>Flash point ASTM C</b>	<b>Pour point D93 C</b>	<b>Kinematic Viscosity</b>		<b>Viscosity Index</b>	<b>TBN mgKOH/ g</b>
					<b>40 C</b>	<b>100 C</b>		
<b>LEOPARD RX</b>	<b>15W/40</b>	<b>0,890</b>	<b>220</b>	<b>-30</b>	<b>110</b>	<b>13.5</b>	<b>120</b>	<b>7.5</b>