

## PRODUCT INFORMATION

**PRODUCT NAME** VASOIL MULTIDIESEL 10W/40

**DESCRIPTION** **MULTIDIESEL 10W/40** introduces improved semi synthetic oil for use in the new generation of Diesel and Gasoline engines operating under very severe duty, or subject to deposit formation or excessive wear due to design characteristics. Formulated from high quality base stock of high viscosity index and low pour point, treated with a carefully selected and balance percentage of the latest additives to impact superior detergency together with high dispersant antioxidant, antiwear and antifoam properties.  
The **MULTIDIESEL 10W/40** is marketed in Viscosity grade - SAE 10W/40.

## PRODUCT USE

**MULTIDIESEL 10W/40**, is specially formulated for modern normally aspirated and supercharged turbo **Diesel and Gasoline engines** operating under very severe duty. This Multigrade oil is able to give efficient lubrication when starting-up the engine, reducing friction, resist to sludge formation as well as enabling reduction of fuel consumption and air pollution.

## SPECIFICATIONS

**MULTIDIESEL** meets the requirements of the following specifications:

API CI-4 / CH-4 / CG-4	API SL / SJ	CUMMINS 20076/77/78
ACEA E7 / A3 / B3 / B4	VOLVO VDS 3	CATERPILLAR ECF - 1A
MB p228.3 / 229.1	MTU TYPE 2	RENAULT RLD - 2
MAN 3275	MACK EOM PLUS	DETROIT DIESEL 93K215
JASO DHD-1	DEUTZ DQC-III-05	

## CHARACTERISTICS ( TYPICAL PROPERTIES )

VASOIL BRAND	SAE Viscosity Grade	Mass Density @ 15 C Kg / lt	Flash point ASTM C	Pour point D93 C	Kinematic Viscosity		Viscosity Index	TBN mgKOH/ g
					40 C	100 C		
MULTIDIESEL	10W/40	0,880	240	-33	105	15	150	10,7