

PRODUCT INFORMATION

PRODUCT NAME VASOIL MULTIDIESEL PLUS 10W/40

DESCRIPTION **MULTIDIESEL PLUS 10W/40** introduces improved synthetic blend oil for use in Euro 4 (and previous) Diesel engine models operating under very severe duty, or subject to deposit formation or excessive wear due to design characteristics. Formulated from high quality base stock of high viscosity index and low pour point, treated with a carefully selected and balance percentage of the latest additives to impact superior detergency together with high dispersant antioxidant, antiwear and antifoam properties.
The **MULTIDIESEL PLUS 10W/40** is marketed in Viscosity grade - SAE 10W/40.

PRODUCT USE

MULTIDIESEL PLUS 10W/40, is specially formulated for modern normally aspirated and supercharged turbo **Diesel engines** operating under very severe duty. This Multigrade oil is able to give efficient lubrication when starting-up the engine, reducing friction, resist to sludge formation as well as enabling reduction of fuel consumption and air pollution.

SPECIFICATIONS

MULTIDIESEL PLUS meets the requirements of the following specifications:

ACEA E4 / E7-12	VOLVO VDS 3	CUMMINS 20078
API CI-4	MTU III	GLOBAL DHD-1
MB p228.5	MACK EOM PLUS	RENAULT RXD/RLD - 2
MAN 3277	DEUTZ IV-10	DETROIT DIESEL 93K215
MAN 3377		

CHARACTERISTICS (TYPICAL PROPERTIES)

VASOIL BRAND	SAE Viscosity Grade	Mass Density @ 15 C Kg / lt	Flash point ASTM C	Pour point D93 C	Kinematic Viscosity		Viscosity Index	TBN mgKOH/ g
					40 C	100 C		
MULTIDIESEL PLUS	10W/40	0,875	240	-33	105	15	150	12.5