

PRODUCT INFORMATION

PRODUCT NAME VASOIL MULTI-PLUS

DESCRIPTION **MULTI-PLUS 10W/40** is a part synthetic lubricants for use in Gasoline and small Diesel engines operating under very severe duty, or excessive wear due to design characteristics. They are formulated from high quality base stock of high viscosity index and low pour point, treated with a carefully selected and balance percentage of the latest additives to impact superior detergency together with high dispersant antioxidant, antiwear and antifoam properties.

PRODUCT USE

MULTI-PLUS 10W/40 is specially formulated for modern normally aspirated and supercharged turbo Gasoline and small Diesel engines operating under very severe duty. These Multigrade oil are able to give efficient lubrication when starting-up the engine, reducing friction, resist to sludge formation as well as enabling reduction of fuel consumption and air pollution.

SPECIFICATIONS

MULTI-PLUS 10W/40 meets the requirements of the following specifications:

- API SL/CF/CF- 4
- JASO MA

CHARACTERISTICS (TYPICAL PROPERTIES)

VASOIL BRAND	SAE Viscosity Grade	Mass Density @ 15 C Kg / lt D7777	Flash point IP 35 C	Pour point ASTM D97 C	Kinemat Viscosit ASTM D445 40 C	Kinemat Viscosit ASTM D445 100 C	Visco sity Index	CCS @ -25 ASTM 5293	TBN mgKOH/gr ASTM D2896
MULTI- PLUS	10W/40	0,87	230	- 30	100	14.5	150	6500	7.6