

PRODUCT INFORMATION

PRODUCT NAME VASOIL MULTI-PLUS - SYNT

DESCRIPTION **MULTI-PLUS - SYNT** introduces premium quality “Full SAPS” synthetic blend oil for use in the new generation of Gasoline and small Diesel engines operating under very severe duty, or excessive wear due to design characteristics. Formulated from high quality base stock treated with a carefully selected and balance percentage of the latest additives to impact superior detergency together with high dispersant antioxidant, antiwear and antifoam properties.

The **MULTI-PLUS - SYNT** range is marketed in Viscosity grades
- **SAE 5W/30** and - **SAE 5W/40**.

PRODUCT USE

MULTI-PLUS - SYNT, 5W/30 and 5W/40 are specially formulated for modern normally aspirated and supercharged turbo Gasoline and small Diesel engines operating under very severe duty. These Multigrade oils are able to give efficient lubrication when starting-up the engine, reducing friction, resist to sludge formation as well as enabling reduction of fuel consumption and air pollution.

SPECIFICATIONS

MULTI-PLUS - SYNT range meets the requirements of the following specifications:

- API SL/CF

CHARACTERISTICS (TYPICAL PROPERTIES)

VASOIL BRAND	SAE	Mass	Flash	Pour	Kinematic	Viscosity	Viscosity	TBN
	Viscosity	Density	point	point				mgKOH
	Grade	@ 15 C	ASTM	D93	40 C	100 C	Index	g
		Kg / lt	C	C				
MULTIPLUS	5W/40	0,875	230	-36	85.5	14.5	177	7.6
SYNT	5W/30	0,870	220	-36	70	12	169	7.6