

PRODUCT INFORMATION

PRODUCT NAME VASOIL MULTI-PLUS

DESCRIPTION **MULTI-PLUS 10W/40** is a semi synthetic lubricants for use in Gasoline and small Diesel engines operating under very severe duty, or excessive wear due to design characteristics. They are formulated from high quality base stock of high viscosity index and low pour point, treated with a carefully selected and balance percentage of the latest additives to impact superior detergency together with high dispersant antioxidant, antiwear and antifoam properties.

PRODUCT USE

MULTI-PLUS 10W/40 is specially formulated for modern normally aspirated and supercharged turbo Gasoline and small Diesel engines operating under very severe duty. These Multigrade oil are able to give efficient lubrication when starting-up the engine, reducing friction, resist to sludge formation as well as enabling reduction of fuel consumption and air pollution.

SPECIFICATIONS

MULTI-PLUS 10W/40 meets the requirements of the following specifications:

- ACEA A3 / B3 / B4
- API SL/CF
- MB 229.1
- RN0700
- VW 505.00

CHARACTERISTICS (TYPICAL PROPERTIES)

VASOIL BRAND	SAE	Mass	Flash	Pour	Kinematic	Viscosity	Viscosity	TBN
	Viscosity	Density	point	point				mgKOH
	Grade	@ 15 C	ASTM	D93			Index	g
		Kg / lt	C	C	40 C	100 C		
MULTI-PLUS	10W/40	0,875	230	-30	100	14.5	142	10