

PRODUCT INFORMATION

PRODUCT NAME VASOIL ULTRA-DIESEL

DESCRIPTION **ULTRA-DIESEL** introduces a premium quality synthetic blend low saps Diesel engine oil for use in EURO V and EURO VI engines with DPF and SCR nox reduction systems. Formulated from high quality base stock of high viscosity index , low NOACK and low pour point, treated with a carefully selected and balance percentage of the latest additives to impact superior detergency together with high dispersant antioxidant, antiwear and antifoam properties.
The **ULTRA-DIESEL** is marketed in Viscosity grade - **SAE 10W/40 and SAE 10W/30**.

PRODUCT USE

ULTRA-DIESEL, is specially formulated for all types of low emissions diesel engines us EURO 4,5&6.and for modern normally aspirated and supercharged turbo Diesel engines operating under very severe duty. This Multigrade oil is able to give efficient lubrication when starting-up the engine, reducing friction, resist to sludge formation as well as enabling reduction of fuel consumption and air pollution.

SPECIFICATIONS

ULTRA-DIESEL meet the requirements of following specifications

ACEA E6 -16	ACEA E7 -16	ACEA E9 -16
API CI - 4	VOLVO VDS 3	CUMMINS CES 20076/77
MB 228.51	MTU CATEGORY 3.1	DEUTZ DQC IV-10LA
MAN M 3477 – MAN 3271-1	RENAULT RLD-2	MACK EO-N PREMIUM PLUS

CHARACTERISTICS (TYPICAL PROPERTIES)

VASOIL BRAND	SAE	Mass	Flash	Pour	Kinematic	Viscosity	Viscosity	TBN
	Viscosity	Density	point	point				mgK
	Grade	@ 15 C	ASTM	D93	40 C	100 C	Index	OH/ g
ULTRA- DIESEL	10W/40	0,87	240	-30	100	15	157	10.4
	10W/30	0.86	230	-40	80	12	145	10.4