

PRODUCT INFORMATION

PRODUCT NAME VASOIL ULTRA SYNT F

DESCRIPTION **ULTRA-SYNT F** is premium quality full synthetic mid saps oil for use in the new generation of Gasoline and small Diesel engines operating under very severe duty, or excessive wear due to design characteristics.

Formulated from high quality Synthetic base stock treated with a carefully selected and balance percentage of the latest additives to impact superior detergency together with high dispersant antioxidant, antiwear and antifoam properties.

The **ULTRA-SYNT F** is marketed in Viscosity grade - **SAE 0W/30**.

PRODUCT USE

ULTRA-SYNT F, is a synthetic engine oil with outstanding Fuel Economy properties for Gasoline and small Diesel engines including those equipped with a DPF and 3 way catalyts.

ULTRA-SYNT F, is specifically developed for latest technology FORD diesel engines requiring a SAE 0W-30 lubricant and the specification WSS-M2C950-A.

SPECIFICATIONS

ULTRA-SYNT F 0W-30 meet the requirements of following specifications:

- FORD WSS-M2C950-A
- ACEA C2

CHARACTERISTICS (TYPICAL PROPERTIES)

VASOIL BRAND	SAE Viscosity Grade	Mass Density @ 15 C Kg / lt	Flash point D92 C	Pour point D97 C	Kinematic Viscosity		Viscosity Index	TBN mgKOH/ g
					40 C	100 C		
ULTRA-SYNT F	0W/30	0,848	226	-45	45	9.6	203	8