

PRODUCT INFORMATION

PRODUCT NAME VASOIL VISCOPLUS - SYNT.

DESCRIPTION **VISCOPLUS - SYNT** introduces premium quality “Full SAPS” synthetic oil for use in the new generation of Gasoline and small Diesel engines operating under very severe duty, or excessive wear due to design characteristics. Formulated from high quality group III base stock treated with a carefully selected and balance percentage of the latest additives to impact superior detergency together with high dispersant antioxidant, antiwear and antifoam properties.

The **VISCOPLUS SYNT** range is marketed in Viscosity grades
- **SAE 5W/30** and - **SAE 5W/40**.

PRODUCT USE

VISCOPLUS -SYNT, 5W/30 and 5W/40 are specially formulated for modern normally aspirated and supercharged turbo Gasoline and small Diesel engines operating under very severe duty. These Multigrade oils are able to give efficient lubrication when starting-up the engine, reducing friction, resist to sludge formation as well as enabling reduction of fuel consumption and air pollution.

SPECIFICATIONS

VISCOPLUS -SYNT range meets the requirements of the following specifications:

	SAE 5W/40		SAE 5W/30
API SL/SM/SN / CF	ACEA A3/B4 - 12	BMW LONGLIFE -01	API. SL
MB 229.3/229.5/226.5	PORCHE A 40	PSA B 712296	ACEA A1/B1/A5/B5
VW 502 / 505	RN 0700 / RN 0710	GM-LL-B-025	WSS-M2C913-C/D

CHARACTERISTICS (TYPICAL PROPERTIES)

VASOIL BRAND	SAE Viscosity Grade	Mass	Flash	Pour	Kinematic	Viscosity	Viscosity	TBN
		Density	point	point			Index	mgKOH
		@ 15 C Kg / lt	ASTM C	D93 C	40 C	100 C		g
VISCOPLUS SYNT	5W/40	0,875	230	-45	85.5	14.5	177	10
	5W/30	0,87	220	-45	70	12	169	10