

# TECHNICAL DATA SHEET



## PRODUCT INFORMATION

**PRODUCT NAME** VASOIL ATF CVT

**DESCRIPTION** **ATF CVT** is an extra high performance full synthetic automatic CVT transmission fluid developed to meet the requirements of the Asian, American and European car manufacturers.

## PRODUCT USE & PROPERTIES

**ATF CVT** is recommended for most passenger car and commercial automatic CVT transmissions. **Provide:**

- Extended friction durability to provide superior anti-shudder performance and enhanced driving comfort.
- A well-balanced, high level of both torque capacity and anti-shudder performance,
- Higher safety factor
- Longer transmission life
- Extended service interval
- Excellent extreme pressure and anti-wear performance for the better protection of transmission
- Enhanced oxidative stability for longer fluid life and extended service interval
- Seal compatibility for better leakage prevention.

## ATF CVT "SUITABLE FOR USE" TABLE

Audi Multitronic	Mitsubishi CVTF-J1,(MMC Diaqueen CVT Fluid J1)
BMW Mini Cooper EZL 799/799A	Mitsubishi CVTF-J4 and -J4+(MMC Diaqueen CVT)
Daihatsu AMMIX CVTF DFE	Mitsubishi ( Diaqueen) SP-III (CVT model only)
Daihatsu AMMIX CVT Fluid DC, Fluid DFC	Nissan NS-1, -2, -3
Daihatsu Fluid TC	Punch CVT
Dodge/Jeep/Chrysler NS-2,	Subaru iCTV, iCVT FG, ECVT,
Dodge/Chrysler/Jeep/ Mopar CVT+4.	Subaru Lineartronic chain CVT and CVT II Fluid
GM/Saturn DEX-CVT	Subaru Lineartronic High Torque (HT) CVT Fluid
Honda HMMF (without starting clutch), HCF2	Subaru NS-2
Honda Z-1 CVT without starting clutch, not SFU	Suzuki CVTF TC ,CVTF 3320
Hyundai/Kia CVT-J1, SP III (CVT model)	Suzuki NS-2 ,CVT Green 1/2/1V
Idemitsu CVTS-EX1	Toyota CVTF TC & CVTF FE
Mazda JWS 3320	VW/Audi TL 521 16 (G 052 516)
Mini Cooper EZL 799/EZL 799A/ZF CVT V1	VW/Audi TL 521 80 (G 052 180 A2)

## CHARACTERISTICS ( TYPICAL PROPERTIES )

VASOIL BRAND	SAE Viscosity Grade	Mass Density @ 15 C Kg / lt	Flash point ASTM C	Pour point D93 C	Kinematic Viscosity		Viscosity Index
					40 C	100 C	
ATF CVT		0,855	180	-45	38	7.5	169

Vasoil Co Ltd

Nikou Pattichi 52 Street ,3071 Limassol, Cyprus.

Email [vasoil@vasoil.com.cy](mailto:vasoil@vasoil.com.cy) , tel: 0035725334488

