

TECHNICAL DATA SHEET



PRODUCT INFORMATION

PRODUCT NAME VASOIL ATF SP 3

DESCRIPTION ATF SP 3 is an extra high performance full synthetic automatic transmission fluid develop to meet the requirements of the Asian, American and European car manufacturers.

PRODUCT USE

ATF SP 3 is recommended for most passenger car and commercial automatic transmissions. It is also suitable for power steering systems, hydraulic applications , some manual transmissions where an automatic transmission fluid is specified and anywhere fluid with the following specification request.

SPECIFICATIONS

ATF SP 3 meet the requirements of the following specifications:

JASO M315 TYPE 1A	MAZDA ATF D-III, ATF M-3	VOITH 55.6335
TOYOTA TYPE T,T-II,T-III&T-IV	SUBARU ATF	ZF TE-ML 14A
TOYOTA WS,TOYOTA T.P. D2	DAIHATSU ALUMIX ATF M	MAN 339 TYPE Z-1
NISSAN MATIC FLUID C,D & J	HYUNDAI Rebrands MITS.	DEXRON IID/E & TASA
MITSUBISHI SP -II & SP -III	KIA Rebrands MITSUBIS.	DEXRON III G
ISUZU BESCO ATF -II & ATF-III	GM DAEWOO	DEXRON III H
SUZUKI ATF OIL&ATFSPECIAL	ATF + 4	ALLISON C-4
HONDA ATF Z1		MERCON

CHARACTERISTICS (TYPICAL PROPERTIES)

VASOIL BRAND	SAE Viscosity Grade	Mass Density @ 15 C Kg / lt	Flash point ASTM C	Pour point D93 C	Kinematic Viscosity		Viscosity Index
					40 C	100 C	
ATF SP 3		0,855	180	-45	38	7.5	169

Vasoil Co Ltd

Nikou Pattichi 52 Street ,3071 Limassol, Cyprus.

Email vasoil@vasoil.com.cy , tel: 0035725334488

