

## PRODUCT INFORMATION

**PRODUCT NAME** VASOIL GREASE VASPLEX G

**DESCRIPTION** **VASPLEX G** is a high quality, calcium based grease with graphite , enriched with a special combination of additives which provides outstanding protection from oxidation, wear, rust , corrosion and excellent water resistance properties.

## PRODUCT USE

**VASPLEX G** is recommended for lubrication of medium duty roller and plain bearings operating at a temperature from -10°C to +80°C and where water are present.

## ADVANTAGES

1. High resistance to water washing.
2. Excellent fluidity in low temperature
3. Efficient oxidation stability.
4. Excellent protection from rust, wear and corrosion.

## SPECIFICATIONS

DIN 51825 :GF 2 E-10

## CHARACTERISTICS ( TYPICAL PROPERTIES )

VASPLEX GREASE	ASTM	
Soap type		calcium
NLGI Number		2
Drop Point, °C min	D- 566	90
Base Oil Viscosity @40°C	D-445	90
Cone Penetration @25°C mm-1 (worked 60 strokes)	D-217	265-295
Copper Corrosion Cu,	D-4048	1b
Operating temperature °C		-10°C to +80°C
Oil separation % max	D-1742	5
Rust Prevention	D-1743	pass
Color		BLACK