

## PRODUCT INFORMATION

**PRODUCT NAME** VASOIL STOU 15W/40

**DESCRIPTION** **STOU 15W/40** is high quality multifunctional, agricultural oil, having a viscosity of SAE 15W/40.  
It is intended for four main applications:

- as an engine oil for diesel naturally aspirated and turbo charged engines
- as a transmission oil for manual gears, semi-automatic transmissions (with and without torque converter) and hydrostatic transmissions
- as an hydraulic oil in automotive, agriculture and construction equipment
- for oil immersed brakes. The oil contains a friction modifier which avoids vibration and noise (squawk) when the brakes are operated.

## PRODUCT USE

**STOU 15W/40** is intended for use in the tractors and other agricultural machines, including cotton pickers. It is also recommended for use in gearboxes and transmissions where a GL-4 oil is specified.

## SPECIFICATIONS

**STOU 15W/40 15W/40** is a multigrade oil, which meets the following specifications:

API CD / SE	API GL-4	MF M 1135
ZF TE ML 06A	FORD M2C159B,C	MF M 1139

## CHARACTERISTICS ( TYPICAL PROPERTIES )

VASOIL BRAND	SAE Viscosity Grade	Mass Density @ 15 C Kg / lt	Flash point ASTM C	Pour point D93 C	Kinematic Viscosity		Viscosity Index	TBN mgKOH/ g
					40 C	100 C		
STOU	15W/40	0.88.5	240	-25	115	14.5	128	9.4