

PRODUCT INFORMATION

PRODUCT NAME VASOIL SYNTCUT OIL

DESCRIPTION **SYNT CUT OIL** , is a high quality, water soluble Semi synthetic cutting oil emulsion, produced by HVI and VHVI base oils of an exceptional quality level, and enrich with additives which protect from rust, corrosion and bacterium development. Its outstanding formulation provides excellent lubrication properties and effective cooling.

PRODUCT USE

VASOIL SYNT CUT OIL is recommended for use on both ferrous and non-ferrous metals in a wide variety of operations including grinding, milling, turning and drilling. It's the ideal solution in application, which requires a combination of lubrication cooling and rust protection properties. Recommended ratio 3.5% - 10%.

- 1.Efficient lubrication properties
- 2.Effective cooling properties
- 3.Outstanding protection from rust and corrosion
- 4.Increased tool life
- 5.Non-staining
- 6.Effectiveness in a wide variety of machining operations

SPECIFICATIONS

- VV-C-846

CHARACTERISTICS (TYPICAL PROPERTIES)

VASOIL BRAND	ISO	Mass	Flash	Pour	Kinematic	Viscosity	PH @3% Emulsion	PH %
	Viscosity	Density	point	point				
	Grade	@ 15 C	ASTM	D93	40 C	100 C		
		Kg / lt	C	C				
SYNT CUT OIL		0,97	194	-6	58	7.7	9,5	6.7