

PRODUCT INFORMATION

PRODUCT NAME VASOIL UTTO 15W/30

DESCRIPTION **UTTO 15W/30** is high quality Universal tractor transmission oil, having a viscosity Of SAE 15W/30.
It is indented for four main applications:

- as a transmission oil for manual gears, semi-automatic transmissions (with and without torque converter) and hydrostatic transmissions
- as an hydraulic oil in automotive, agriculture and construction equipment
- for oil immersed brakes. The oil contains a friction modifier which avoids vibration and noise (squawk) when the brakes are operated.
- as an engine oil for diesel naturally aspirated and turbo charged engines

PRODUCT USE

UTTO 15W/30 is intended for use in tractors and other agricultural machines, including cotton pickers. It is also recommended for use in gearboxes and transmissions where a GL-4, SAE 80W oil is specified.

SPECIFICATIONS

UTTO 15W/30 is a multigrade oil, which meets the following specifications:

API GL-4, SAE80W	API CD / SE	MF M 1135
ZF TE ML 06A	FORD M2C159B,C	MF M 1139

CHARACTERISTICS (TYPICAL PROPERTIES)

VASOIL BRAND	SAE Viscosity Grade	Mass Density @ 15 C Kg / lt	Flash point ASTM C	Pour point D93 C	Kinematic Viscosity		Viscosity Index	TBN mgKOH/ g
					40 C	100 C		
UTTO	15W/30	0,87.5	230	-25	74,0	10,5	107,6	9.4