

PRODUCT INFORMATION

PRODUCT NAME VASOIL VAS-AIRCOM

DESCRIPTION **VAS-AIRCOM** is a fine quality air compressor lubricant, with a specially balanced additive combination. It is formulated to meet high-output, hot running reciprocating compressors. It protects from carbon and deposit formation.

1. Exceptional resistance to oxidation
2. Less carbon and deposit formation
- 3.Reduces fire and explosion hazards
- 4.Low volatility
- 5.Longer life of up to 4000 hours (where allowed by manufacturers) even when operating at maximum discharge temperatures of up to 100°C
- 6.Excessive resistance to the formation of emulsion with water
- 7.Reduced operation and maintenance cost

PRODUCT USE

VAS-AIRCOM is recommended to be use with both (rotary and reciprocating types) compressors where the exhaust temperatures reach as high as 220 C.

VAS-AIRCOM 46 ... 68 in particular for screw-type and rotary compressors

VAS-AIRCOM 100...150 for heavy loaded piston compressors

SPECIFICATIONS

VAS-AIRCOM meet the requirements of the following specifications:

- DIN 51506 VD - L

CHARACTERISTICS (TYPICAL PROPERTIES)

VASOIL BRAND	ISO Viscosity Grade	Mass Density @ 15 C Kg / lt	Flash point ASTM C	Pour point D93 C	Kinematic Viscosity		Viscosity Index
					40 C	100 C	
VAS-AIRCOM	32	0,870	210	-18	32	5.46	106
	46	0,875	230	-18	46	6.86	104
	68	0,880	247	-18	68	8.80	102
	100	0,886	257	-18	100	11.38	100
	150	0,889	263	-18	150	14.83	98