

PRODUCT INFORMATION

PRODUCT NAME VASOIL VASLIDEWAY OILS

DESCRIPTION **VASLIDEWAY OILS** is an universal machine tool lubricant, based on mineral oil, under addition of several additives to obtain the following properties:

- a very strong adhesion to (vertical) slides
- superior “stick-slip” properties
- very good anti-wear, anti-rust and anti-corrosion properties
- good demulsification properties

PRODUCT USE

VASLIDEWAY OILS This oil is a machine tool lubricant specially designed for slideway lubrication, with emphasis on superior stick-slip properties. This machine tool lubricant also meets the requirements of hydraulic systems, gear oils.

SPECIFICATIONS

VASLIDEWAY OILS meet the requirements of the following specifications:
- DIN 51524/ DIN51517

CHARACTERISTICS (TYPICAL PROPERTIES)

| VASOIL BRAND | ISO Viscosity Grade | Mass Density @ 15 C Kg / lt | Flash point ASTM C | Pour point D93 C | Kinemati c | | Viscosity Index |
|--------------|---------------------------|--------------------------------------|-----------------------------|---------------------------|---------------|-------|--------------------|
| | | | | | 40 C | 100 C | |
| VASLIDEWAY | 68 | 0,880 | 230 | -15 | 68 | 8,5 | 97 |
| OILS | 100 | 0,883 | 235 | -15 | 100 | 11,13 | 96 |
| | 150 | 0,887 | 238 | -15 | 150 | 14,64 | 96 |
| | 220 | 0,895 | 240 | -15 | 220 | 18,9 | 96 |
| | 320 | 0,910 | 250 | -15 | 320 | 24.1 | 96 |
| | 460 | 0,920 | 260 | -9 | 460 | 30,6 | 96 |