

PRODUCT INFORMATION

PRODUCT NAME VASOIL VASLUB OILS

DESCRIPTION **VASLUB OILS** are premium quality mineral oils. They are refined to provide a high viscosity-index, good oxidation stability and improved demulsibility. They also have good temperature flow characteristics.

PRODUCT USE

VASLUB OILS are used for applications where additive-treated oils are not required. **VASLUB OILS** are recommended for the lubrication of plain and rolling – element bearings as well as for spur, bevel, helical and worm gearboxes where temperatures and loadings are moderate. The grade to be chosen should be that recommended by the system designer.

SPECIFICATIONS

- HVI Mineral Oils

CHARACTERISTICS (TYPICAL PROPERTIES)

| VASOIL BRAND | ISO Viscosity Grade | Mass Density @ 15 C Kg / lt | Flash point ASTM C | Pour point D93 C | Kinematic Viscosity | | Viscosity Index |
|--------------|---------------------------|--------------------------------------|-----------------------------|---------------------------|---------------------|-------|--------------------|
| | | | | | 40 C | 100 C | |
| VASLUB OILS | 22 | 0,870 | 200 | -10 | 22 | 4,2 | 90 |
| | 32 | 0,872 | 205 | -10 | 32 | 5,4 | 103 |
| | 46 | 0,875 | 240 | -10 | 46 | 6,8 | 101 |
| | 68 | 0,884 | 250 | -10 | 68 | 8,7 | 100 |
| | 100 | 0,890 | 260 | -10 | 100 | 11,4 | 100 |
| | 150 | 0,891 | 265 | -10 | 150 | 15,0 | 100 |
| | 220 | 0,892 | 271 | -10 | 220 | 18,9 | 96 |
| | 320 | 0,894 | 288 | -8 | 320 | 24.1 | 96 |
| | 460 | 0,896 | 289 | -8 | 460 | 30,6 | 96 |