

PRODUCT INFORMATION

PRODUCT NAME VASOIL VASMAL OIL

DESCRIPTION **VASMAL OIL** is an exceptional quality, non-emulsifiable mineral oil, specially designed to meet the highest performance level. It contains an advance additives combination, which provides excellent lubrication and protection properties, even in the severest machining operations. Due to its outstanding load carrying ability operates ideally under the heaviest machining operations on steel and its alloys.

- 1.Effective resistance to corrosion
- 2.Excellent anti-friction properties
- 3.Outstanding endurance of high pressures
- 4.Long service life
- 5.Excellend tool wear minimizing
- 6.Efficient metal and tool cooling properties
- 7.Very wide range of applications of the industry

PRODUCT USE

VASMAL OIL recommended to be used in very heavy machining operations, which require a non-emulsifiable mineral oil, appropriate for any king of steel and its alloys.

SPECIFICATIONS

- DIN 51515, G.M. LTP-SM 50031 AEI , AGMA R & O

CHARACTERISTICS (TYPICAL PROPERTIES)

VASOIL BRAND	ISO	Mass	Flash	Pour	Kinematic	Viscosity	Viscosity
	Viscosity Grade	Density @ 15 C Kg / lt	point ASTM C	point D93 C			Index
					40 C	100 C	
VASMAL OIL	22	0,867	195	-24	22	4.25	95