

PRODUCT INFORMATION

PRODUCT NAME VASOIL VASMAR 3015 & 4015

DESCRIPTION VASMAR 3015 & 4015 are premium quality trunk piston engine oils used for power generation or propulsion in medium or high speed trunk piston engines burning distillate fuels. They are blended from high quality mineral base oils and selected additive packages with premium anti-corrosion, detergent/dispersant and BN retention properties.

Performance Features

- Exceptional detergent /dispersant properties
- Exceptional cleanliness of crankcase, piston rings and valves
- Corrosion and Wear protection of engine parts (camshaft, bearings)
- High oxidation stability and deposits control
- Good water separation
- Good antifoam properties

PRODUCT USE

VASMAR 3015 & 4015 lubricating oils are recommended for trunk piston engines operating with ISO 8217 type DMA/DMZ/DMB/RMA10 fuels and requiring API CF performance.

They are also suitable for engine reduction gears and bearing lubrication.

SPECIFICATIONS

VASMAR 3015 & 4015 meets the requirements of the following specifications
- API service classification CF.

CHARACTERISTICS (TYPICAL PROPERTIES)

VASOIL BRAND	SAE Grade	Mass Density @ 15 C Kg / lt	Flash point C	Pour point C	Kinem.	Viscosity	Viscos. Index	TBN mgKOH/ g
					cSt at 40 C	cSt at 100 C		
VASMAR 3015	30	0,890	230	-18	95	11.2	101	15
4015	40	0.895	254	-18	139	14.1	99	15