

PRODUCT INFORMATION

PRODUCT NAME VASOIL VASMAR 3030 & 4030 & 4020

DESCRIPTION VASMAR 3030 & 4030 & 4020 are premium performance high alkaline diesel engine oils used in medium or high speed trunk piston diesel engines burning residual fuels with high sulphur content (3-4%). They are blended from high quality mineral base oils and selected additive packages providing premium performance characteristics under severe operating conditions.

Performance Features

- Exceptional detergent /dispersant properties, providing clean piston rings, valves and crankcase
- Excellent alkalinity retention
- Corrosion and Wear protection of engine parts (cylinder liner, camshaft, bearings)
- High thermal and oxidation stability
- Good water separation and centrifuge performance
- Good antifoam properties
- Minimum filter blockage

PRODUCT USE

VASMAR 3030 & 4030 & 4020 lubricating oils are recommended for trunk piston diesel engines (marine and industrial) burning residual fuels with maximum sulphur content of 4%.

SPECIFICATIONS

VASMAR 3030 & 4030 & 4020 meets the requirements of the following specifications
- API service classification CF.

CHARACTERISTICS (TYPICAL PROPERTIES)

VASOIL BRAND	SAE Grade	Mass Density @ 15 C Kg / lt	Flash point C	Pour point C	Kinem.	Viscosity	Viscos. Index	TBN mgKOH/ g
					cSt at 40 C	cSt at 100 C		
VASMAR								
3030	30	0,900	236	-15	103	11.3	98	30
4030	40	0.905	246	-15	145	14.5	98	30
4020	40	0.905	246	-15	145	14.5	98	20