

PRODUCT INFORMATION

PRODUCT NAME VASOIL VASREX EPS OIL

DESCRIPTION **VASREX EPS OIL** are EP (Extreme Pressure) gear oils formulated for hypoid gears and other heavily loaded gears, The selectively balance EP additives maintain their good anti-wear, oxidation stability and anti-rust characteristics even under high load conditions as occur with hypoid gears used in many automotive axles.

VASREX EPS 75W/80 is full synthetic.

PRODUCT USE

VASREX EPS OIL are particularly recommended for lubricating hypoid gears operating under normal conditions for which an EP oil is required.

VASREX EPS OIL can also be used for lubricating gears for earth moving machinery, tractors and other off-road equipment.

SPECIFICATIONS

VASREX EP OILS meet the requirements of the following specifications:

API GL-4	Mass fraction of mechanical impurities, %, not more than : 0,025	Mass fraction of water, %, not more than : Traces
Mass fraction of phosphorus, %, not less than : 0,08	Corrosion test : Withstands	

CHARACTERISTICS (TYPICAL PROPERTIES)

VASOIL BRAND	SAE Viscosity Grade	Mass Density @ 15 C Kg / lt	Flash point ASTM C	Pour point D93 C	Kinemati c		Viscosity Index
					40 C	100 C	
VASREX EPS OIL	75w/80	0,875	>164	<-50	7.5-8.5	>140	

Issue 7- 2019

Vasoil Co Ltd

Nikou Pattichi 52 Street ,3071 Limassol, Cyprus.

Email vasoil@vasoil.com.cy , tel: 0035725334488

