

PRODUCT INFORMATION

PRODUCT NAME VASOIL VASREX LS OILS

DESCRIPTION **VASREX LS OILS** are outstanding EP (Extreme Pressure) gear oils formulated for differentials that require oils with limited-slip characteristics.
VASREX LS OILS have a good performance at high speeds and high torque levels, with notable noise reduction.

PRODUCT USE

VASREX LS OILS can be used in all types of differential that require this quality level, especially limited-slip (LS) differentials.

SPECIFICATIONS

VASREX LS OILS meet the requirements of the following specifications:

| | | |
|-------------------|--------------|--------------|
| API GL-4 & GL - 5 | ZF TE-ML 05C | ZF TE-ML 12C |
| ZF TE-ML 16E | ZF TE-ML 21C | |

CHARACTERISTICS (TYPICAL PROPERTIES)

| VASOIL BRAND | SAE Viscosity Grade | Mass Density @ 15 C Kg / lt | Flash point ASTM C | Pour point D93 C | Kinematic Viscosity | | Viscosity Index |
|-----------------------|---------------------------|--------------------------------------|-----------------------------|---------------------------|---------------------|-----------|--------------------|
| | | | | | 40 C | 100 C | |
| VASREX LS OILS | 90 | 0,893 | 250 | -15 | 170 | 16 | 97 |
| | 80W/90 | 0,893 | 250 | -30 | 160 | 16 | 103 |