

PRODUCT INFORMATION

PRODUCT NAME VASOIL VASREX SYNT 75W/90

DESCRIPTION VASREX SYNT 75W/90 is full synthetic multipurpose gear lubricant for use in both synchronized manual transmissions, final drives and differentials where either API GL-4 or API GL-5 are specified.

PRODUCT USE

VASREX SYNT 75W/90 may be used in synchronized manual transmissions and final drives/differentials of a wide range of vehicles, commercial vehicle, construction equipment, passenger cars and anywhere API GL-4 or API GL-5 fluids are required

SPECIFICATIONS

VASREX SYNT OILS meet the requirements of the following specifications:

API GL-4 & API GL5	MAN M 3343 Type S	ZF TE-ML 02B / 05B / 07A
API MT-1	MAN 342 S1, S2	ZF TE-ML 12B / 16F / 17B
SAE J2360	MB 235.8	ZF TE-ML 19C / 21B
Ford WSD-M2C200-C	Mack GO-J, MACK GO-J plus	Scania STO 1:0
DAF	IVECO	ARVIN MERITOR 0-76-N

CHARACTERISTICS (TYPICAL PROPERTIES)

VASOIL BRAND	SAE Viscosity Grade	Mass Density @ 15 C Kg / lt	Flash ASTM C	Pour D93 C	Kinematic Viscosity		Viscosity Index
					40 C	100 C	
VASREX SYNT OILS	75w/90	0,875	200	-45	76	16,5	234