

## PRODUCT INFORMATION

**PRODUCT NAME** VASOIL VASREX SYNT

**DESCRIPTION** VASREX SYNT is full synthetic multipurpose gear lubricant for use in both synchronized manual transmissions, final drives and differentials where either API GL-4 or API GL-5 are specified.

## PRODUCT USE

VASREX SYNT may be used in synchronised manual transmissions and final drives/differentials of a wide range of vehicles, commercial vehicle, construction equipment, passenger cars and anywhere API GL-4 or API GL-5 fluids are required

## SPECIFICATIONS

VASREX SYNT OILS meet the requirements of the following specifications:

API GL-4 & API GL5	MAN M 3343 Type S	ZF TE-ML 02B / 05B / 07A
API MT-1	MAN 341 Type E-3	ZF TE-ML 12B / 16F / 17B
SAE J2360	MB 235.8	ZF TE-ML 19C / 21B
MIL-PRF-2105E	Mack GO-J	Scania STO 1:0
DAF	IVECO	ARVIN MERITOR 0-76-N

## CHARACTERISTICS ( TYPICAL PROPERTIES )

VASOIL BRAND	SAE Viscosity Grade	Mass Density @ 15 C Kg / lt	Flash ASTM C	Pour D93 C	Kinematic Viscosity		Viscosity Index
					40 C	100 C	
VASREX SYNT	75w/90	0,875	200	-45	83	17	223
	75w/80	0.87	200	-45	55	9	143